



OUTLET:
 bended joint 1/2" - 12 mm (0.47in)
 straight joint 1/2" - 16 mm (0.63in)

INLET:
 bended joint 1/2" - 12 mm (0.47in)
 straight joint 1/2" - 16 mm (0.63in)

Dimensions	215 mm x 361 mm x 315 mm (h)		8.46in x 14.21in x 12.4in (h)	
Weight	12,2 kg		26,9 lb	
Voltage-Frequency	230V - 50Hz	230V - 60Hz	115V - 60Hz	
Current Consumption	1,7A	1,3A	1,9A	
Compressor Power	1/8 HP			
Power Consumption (Cooling)	150 W		510 Btu/h	
Power Consumption (Heating)	\			
Cooling Capacity *	220 W		750 Btu/h	
Min and Max Water Flow	300 l/h - 500/h		80 Usgal/h - 132 Usgal/h	
Air Flow	\			
Maximum Exchanger's Pressure	0,5 bar		7,25 PSI	
Ambient Temperature Range	5°C - 38°C		41°F - 100°F	
Water Temperature	18°C - 22°C		64°F - 72°F	
Certification \ Protection Grade	CE \ IPX4			
Refrigerant	R134a			
* reported value refers to the following condition: room temperature 30°C (86°F), water temperature 20°C (68°F)				
All data are approximate and may be changed without notice by TECO				

Material:	Drawing: HY 150 – technical data		
Thickness:	File: HY_150_technical_drawing		
Finishing:	Your code:	Code:	
Volume:	Tol.	Scale: 1: 5	Date: 26/10/2017
Approved:	Via A.Sansovino, 35 48124 RAVENNA – ITALY Tel. +39 0544 408333 Fax 280084 http://www.tecoonline.com		
	Drawer: Giulia		

AS BY LAW ENACTED WE RESERVE US THE PROPERTY OF THIS DOCUMENT WITH THE PROHIBITION OF REPRODUCE IT, SAVE IT INTO ARCHIVES SYSTEM, GIVE IT OR HOWEVER LENT IT TO THIRD PARTY WITHOUT OUR AUTHORIZATION. EVERY VIOLATION INVOLVES THE COMPENSATION FOR THE UNDERGONE DAMAGES. WE MAKE RESERVATIONS ABOUT ALL THE RIGHTS DERIVING FROM PATENTS OR MODELS.

Drawer: Modify