

**LUMATEK**  
PROFESSIONAL LIGHTING

# 680W GH TOP LIGHT LED

(RED + BLUE)



The **680W GH Top Light (Red + Blue)** is a very high performance, innovative, slim, compact, powerful and efficient LED for Greenhouse use. This unit was designed for high PPFD target flowering crops, using only the highest grade components allowing you to achieve your goals and correct DLI throughout the year.

3.4  $\mu\text{mol}/\text{J}$

2285  $\mu\text{mol}/\text{s}$  total output

Red + Blue

3.4  
 $\mu\text{mol}/\text{J}$

EFFICACY

2285  
 $\mu\text{mol}/\text{s}$

PPF



# THE 680W GH TOP LIGHT (RED + BLUE)

**PRODUCT CODE:** LUMLED016

**EFFICACY:** 3.4  $\mu\text{mol}/\text{J}$

**PPF:** 2285  $\mu\text{mol}/\text{s}$

**INPUT VOLTAGE:** 200-440V, 50-60HZ

**INPUT POWER:** 680W ( $\pm 2\%$ ) @380V

**INPUT CURRENT:** 1.8A @ 380V 100%

**APPLICATION:** GREENHOUSE

**WATERPROOF & DUSTPROOF:** IP65

**LIFETIME (LED BARS):** +50 000 HRS

**LIGHT DISTRIBUTION:** 100°-120°

**LIGHT SOURCE:** 450nm Blue Diodes Osram GD 2.14;

660nm Red Diodes Osram SQ4.24

**QUANTITY OF DIODES TOTAL:** BLUE 80; RED 480

**DIODES POWER PROPORTION:** BLUE 19%; RED 81%

**DIODES EFFICIENCY:** Blue Osram GD 2.14 2.7  $\mu\text{mol}/\text{J}$ ;

Red Osram SQ4.24 3.85  $\mu\text{mol}/\text{J}$

**DIMMABLE:** Yes with 0-10V Dimmer

**EXTERNAL CONTROL:** With Lumatek Digital Panel Plus 2.0

or Universal Controller 0-10V

**WEIGHT:** 8.8 Kg

**DIMENSIONS:** 653.5 x 253.9 x 117.5mm

**SPECTRUM:** Blue 13,4%; Green 0,13%; Red 86,2%; FAR-RED 0,25%

**THERMAL MANAGEMENT:** Passive Cooling

**POWER FACTOR:** 0.97

**MAX. AMBIENT TEMPERATURE (@ 680W POWER):** 40°C



**BTU:** 2320 BTUs/h

**WARRANTY:** 3 YEARS


**CERTIFICATIONS:**

CE: EN 60598-1:2015/EN 60598-2-1/EN 62031:2008


+A1:2013+A2:2015/EN 62493:2015/EN 62471:2008



## SQD SPECTRUM GRAPH



## DISTRIBUTION CURVE FLUX



## ITEMS INCLUDED IN THE BOX:

- 1 x Lumatek 680W GH Top Light LED (Red + Blue) Fixture
- 1 x Power Cable with Twist-Lock
- 1 x Hanging Set
- 1 x Manual

## EXTERNAL CONTROL

The Lumatek GH Top Light LED fixtures can also be externally controlled with a Lumatek digital lighting controller (Digital Panel Plus 2.0) featuring light timing, automated dimming (1% increments), temperature safety control, Sunrise & Sunset Mode for up to 100 fixtures per controller. Or with any Universal Controller with 0-10V Output.



**For sales support:**  
orders@lumatek-lighting.com

**General contact:**  
info@lumatek-lighting.com

**For technical support:**  
techsupport@lumatek-lighting.com

FOR MORE INFORMATION ON LUMATEK PRODUCTS  
VISIT [WWW.LUMATEK-LIGHTING.COM](http://WWW.LUMATEK-LIGHTING.COM)